

## SUPPORTS

## MODEL SH HEAVY DUTY PERMANENT SUPPORTS

ELV. CODE	HEIGHT ADJ. MIN. (TOP OF SUPPORT)	HEIGHT ADJ. MAX. (TOP OF SUPPORT)	7-21" BF WT. (lbs.)	22-27" BF WT. (lbs.)	28-39" BF WT. (lbs.)	40-51" BF WT. (lbs.)
1	6-1/4"	7-3/4"	12	13	17	18
2	7-3/4"	10-3/4"	13	14	18	19
3	10-3/4"	13-3/4"	14	15	19	20
4	13-3/4"	16-3/4"	17	18	21	23
5	16-3/4"	19-3/4"	18	19	22	24
6	19-3/4"	23-3/4"	22	24	31	35
7	23-3/4"	31-3/4"	27	29	37	40
8	31-3/4"	43-3/4"	31	33	40	44
9	43-3/4"	55-3/4"	40	42	53	59
10	55-3/4"	67-3/4"	45	47	58	64
11	67-3/4"	79-3/4"	50	52	64	69
12	79-3/4"	91-3/4"	57	59	70	75

## HEAVY DUTY SUPPORTS MODEL NO.

SH-4-51

SH-(elevation code\*)-(between frames)

\*See chart at left.

## MINIMUM ELEVATION SUPPORTS MODEL NO.

SH0-5-33

SH0-(elevation code\*)-(between frames)

\*See chart below left.


 MODEL SH  
 3000 lbs. support capacity

## SPECIFICATIONS

► **CONSTRUCTION:** 10 ga. inside and outside channel assemblies; C-3 plates are 7 ga.; cross braces are 10 ga. up to 27" BF and 7 ga. 31" BF and above.

► **WIDTHS:** 7", 9", 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 37", 39", 43", 45", 47", 51" BF only; 54", 57" and 63" BF.

## MODEL SHO HEAVY DUTY

ELEVATION CODE	HEIGHT ADJ. RANGE (TOP OF SUPPORT)	UP TO 27" BF WT. (lbs.)	28"-51" BF WT. (lbs.)
1	3-1/2" — 4-1/8"	13	18
2	4-1/8" — 4-3/4"	13	18
3	4-3/4" — 5-3/8"	13	18
4	5-3/8" — 6"	13	18
5	6" — 6-5/8"	13	18