

# MODEL SM MEDIUM DUTY PERMANENT SUPPORTS

ELEVATION CODE	HEIGHT ADJUSTMENT MIN. (TOP OF SUPPORT)	HEIGHT ADJUSTMENT MAX. (TOP OF SUPPORT)	7-21" BF WT. (lbs.)	22-27" BG WT. (lbs.)	28-39" BF WT. (lbs.)	40-51" BF WT. (lbs.)
1	7-1/4"	10-1/4"	10	11	15	17
2	10-1/4"	13-1/4"	12	13	16	18
3	13-1/4"	16-1/4"	14	15	18	20
4	16-1/4"	22-1/4"	16	17	20	22
5	20-1/4"	26-1/4"	21	23	30	33
6	24-1/4"	36-1/4"	23	25	32	36
7	34-1/4"	46-1/4"	27	29	36	39
8	46-1/4"	58-1/4"	34	36	47	53
9	58-1/4"	70-1/4"	38	40	52	57
10	70-1/4"	82-1/4"	42	44	56	61
11	80-1/4"	92-1/4"	46	48	60	65
12	92-1/4"	104-1/4"	50	52	64	69

## MEDIUM DUTY SUPPORTS MODEL NO. SM-5-39

SM-(elevation code\*)-(between frames)

\*See chart at left

## MINIMUM ELEVATION SUPPORTS MODEL NO. SM0-1-17

SM0-(elevation code\*)-(between frames)

\*See chart below.

## SPECIFICATIONS

► **CONSTRUCTION:** 12 ga. inside and outside channel assemblies; C-3 plates are 10 ga.; cross braces are 10 ga. up to 27" BF and 7 ga. 31" BF and above.

► **WIDTHS:** 7", 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 37", 39", 43", 45", 47" & 51" BF.

MIN. ELEVATION MEDIUM DUTY ELEVATION CODE	HEIGHT ADJ. RANGE (TOP OF SUPPORT)	UP TO 27" BF WT. (lbs.)	27"-51" BF WT. (lbs.)
1	3-1/2" — 4-1/8"	10	17
2	4-1/8" — 4-3/4"	10	17
3	4-3/4" — 5-3/8"	10	17
4	5-3/8" — 6"	10	17
5	6" — 6-3/8"	10	17
6	6-3/8" — 7-1/4"	10	17



MODEL SM  
1500 lbs. support capacity